








保力皮帶（平面傳動皮帶）之特性和型號

型號	尼龍厚度	總厚度 (mm)	重量 (g) 10×1000	延伸2%時 軸負荷 Kgf/寬10mm	最小皮帶 輪徑	皮帶構造	適用範圍
KSG	250	0.8	8	6	25	兩面防水布和非常薄的橡膠層 	圓編機，風車皮帶 紗綻皮帶：緯紗機、精紡機和撚紗機、印刷機、裝釘機、折紙機、自動收票機、自動販賣機、輕負荷輸送及傳動。
	350	0.9	9	10.5	35		
IR	500	1.3	15	15	40		
IRS	6S	1.4	14	23	60		
SG	250	0.8	8	6	25		
	350	0.9	9	10.5	35	兩面防水布及薄橡膠層 	工作母帶、自動車床、空氣精紡機、切線皮帶、高轉速紡織機器、各種紡織機器之傳動：紡織吸塵機、緯紗機、電腦傳動皮帶、木工機械、輕負荷輸送。
	500	1.1	11	15	50		
	750	1.3	14	22.5	75		
	1000	1.6	17	30	100		
L	250	1.4	14	6	25		
	350	1.5	16	10.5	35	兩面防水布及橡膠層 	風扇馬達和其他工業機械、各種紡織切線傳動皮帶、環狀精紡機、瓦楞紙印刷機、製箱機、製罐機、木工機械、一般傳動、輕負荷和重負荷輸送。
	500	1.6	18	15	50		
	750	2.2	25	22.5	75		
	1000	2.5	28	30	100		
LA	1500	3.1	34	45	150		
	2000	3.6	40	60	200	兩面防水布及厚橡膠層 	各種紡織機械切線皮帶、精紡機之傳動、捲紙管機械、紙箱製造機、磨麵粉機、圓錐形皮帶輪傳動、耐磨擦性輸送
	250	2.2	24	6	30		
	350	2.3	26	10.5	40		
	500	2.5	27	15	50		
	750	2.8	30	22.5	75		
M	1000	3.0	33	30	100	兩面防水布及厚橡膠層 	捲紙骨機械、糊摺盒機、合紙機、耐磨性輸送。
	1500	3.5	40	45	150		
	2000	4.0	46	60	200		
	500	3.5	38	15	75		
	750	3.7	41	22.5	95		
HA	1000	4.0	44	30	120	表面為特殊合成橡膠 	糊摺盒機進紙部
	1500	4.5	50	45	170		
	2000	5.0	56	60	220		
	500-3.5	3.5	40	7.5	60		
	500-4	4	43	7.5	60		
XH	500-6	6	59	7.5	80	表面為特殊合成橡膠 	糊摺盒機進紙部
	750-4	4	43	11.3	75		
	1000-4	4	44	15	75		
	1000-5	5	52	15	80		
SE-A-WN		8	102	15	80	表面為特殊合成橡膠 	糊摺盒機進紙部
SE-A-GN							